

SHORT CIRCUIT ISOLATOR



- SURFACE MOUNTING TECHNOLOGY
- RED SHORT CIRCUIT WARNING LED PROTECTS LOOP LINE FROM POSSIBLE SHORT CIRCUIT EVENTS
- 1 UNIT FOR EVERY 20 ADDRESSABLE DEVICES

Qty Per Package | **50**

PRODUCT CODE: M.U.YAN.00032

TECHNICAL DETAILS

OPERATING VOLTAGE	24V-34V DC
QUIESCENT CURRENT	<250µA
SHORT CIRCUIT CURRENT	<3mA
OPERATING TEMPERATURE	-10°C / +55°C
DIMENSIONS	8X8X4 cm

REMOTE LED INDICATOR



- SURFACE MOUNTING TECHNOLOGY
- USED AS THE REMOTE LED INDICATOR OF THE HARD TO SEE DETECTORS DUE TO RAISED CEILING LAYERS OR SUSPENDED CEILING

Qty Per Package | **50**

PRODUCT CODE: M.U.YAN.00033

TECHNICAL DETAILS

OPERATING VOLTAGE	24V-34V DC
OPERATING CURRENT	<5mA
OPERATING TEMPERATURE	-10°C / +55°C
DIMENSIONS	8X8X4 cm

ADDRESS PROGRAMMER



- SURFACE MOUNTING TECHNOLOGY
- USED FOR ADDRESSING ADDRESSABLE FIRE ALARM DEVICES
- CAN BE POWERED BY BATTERY OR ADAPTOR
- AUTOMATIC POWER-OFF FEATURE FOR POWER-SAVING
- 2X16 LCD SCREEN

Qty Per Package | **1**

PRODUCT CODE: M.U.YAN.00045

TECHNICAL DETAILS

INPUT VOLTAGE	9V - 12V DC
BATTERY	9V
EXTERNAL FEEDING	12V DC
OPERATING CURRENT	<50mA
OPERATING TEMPERATURE	-10°C / +55°C
DIMENSIONS	190x150x32 mm