

ADDRESSABLE MANUAL CALL POINT **CE**



STANDARDS
EN54-11: 2001/A1: 2005

PRODUCT CODE: M.U.YAN.00026

- PROCESSOR DESIGN
- SURFACE MOUNTING TECHNOLOGY
- RESET FEATURE
- ADDRESSABLE
- LOOP-POWERED
- MECHANICAL TRIGGER MECHANISM
- WARNING LED

TECHNICAL DETAILS

OPERATING VOLTAGE	24V-34V DC
OPERATING CURRENT	<250µA
OPERATING TEMPERATURE	-10°C / +55°C
MATERIAL	FIREPROOF PLASTIC
DIMENSIONS	10x10x4.5 cm

Qty Per Package | **50**

ADDRESSABLE MANUAL CALL POINT WITH ISOLATOR



PRODUCT CODE: M.U.YAN.00042

- PROCESSOR DESIGN
- SURFACE MOUNTING TECHNOLOGY
- RESET FEATURE
- BUILT-IN SHORT CIRCUIT ISOLATOR
- ADDRESSABLE
- LOOP-POWERED
- MECHANICAL TRIGGER MECHANISM
- WARNING LED

TECHNICAL DETAILS

OPERATING VOLTAGE	24V-34V DC
OPERATING CURRENT	<250µA
OPERATING TEMPERATURE	-10°C / +55°C
MATERIAL	FIREPROOF PLASTIC
DIMENSIONS	10x10x4.5 cm
COLOR	RED

Qty Per Package | **50**